



PREP STATIONS

SPECIALTY DIPPING CABINET MODELS DC

Self-contained ice cream storage and dipping cabinet with mechanically cooled syrup rail. These units are offered in a variety of lengths and capacities to meet your needs. The single opening mechanically cooled raised syrup rail provides easy access to syrups and toppings. One piece die-formed 16 gauge stainless steel top is available with slide-top or flip-top cover(s) providing easy access to the ice cream storage compartment. All models come standard with concealed casters.

SHORT FORM SPEC: Randell DC series ice cream dipping cabinets with slide-top or flip-top cover and electronically controlled natural R290 refrigeration system. Conductive cooled storage compartment and syrup rail complete with syrup pumps and fruit jars with ladles. All units include stainless steel front and end panels along with covered corner stainless steel interior storage compartment. All unit shipped on factory installed concealed casters.

AVAILABLE MODELS:

Slide-Top:

DCST-36-SR7
DCST-44-SR9
DCST-54-SR11

Flip-Top:

DCFT-36-SR7
DCFT-44-SR9
DCFT-54-SR11

STANDARD FEATURES:

- Cold-wall conductive cooled base storage and syrup rail
- Electronically controlled temperature
- Syrup pumps and fruit jars included
- Natural R290 refrigeration system
- Stainless steel coved interior base storage compartment
- Foamed in place "CFC free" urethane insulation
- Concealed casters

REFRIGERATION SYSTEM: All models will utilize state of the art, energy efficient R290 compressor system with (0) ozone depletion potential (ODP) and (3) global warming potential (GWP). Units are conductively cooled by coldwall wrapped base storage compartment and syrup rail. Temperature is managed by electronic controller, metered using capillary tube system. Unit totally prewired and to be supplied with 8' cordset (NEMA 5-15P) for 115V operation.

CABINET EXTERIOR: Top to be one piece of die formed 16 gauge stainless steel with 2.5" nosing. Slide-Top models to have recessed removable poly lids. Flip-Top models to have die stamped cut-outs with raised rims, fitted with removable, hinged, insulated lids. Exterior body to be corrosion resistant steel. Front panels to be removable, constructed of 22 gauge die-stamped stainless steel. Louver panel to be die-stamped stainless steel. Work surface to be at 36" work height. Concealed casters mounted to full length channel frame assembly which is integrally welded to bottom of body assembly. Casters can be moved left to right to avoid floor obstacles.

CABINET INTERIOR: Unit interior to be stainless steel, with cover corners, interior sides to be wrapped with refrigeration lines mounted to unit body. Unit insulation to be CFC free foamed in place urethane.

Certifications:  

PROJECT NAME:	
LOCATION:	
ITEM NO:	
QTY:	
MODEL NO:	
AIA NO:	
SIS NO:	
CSI SECTION:	11400



Model DCST-44-SR9 shown


ADDITIONAL RESOURCES:

[Request A Quote](#)


[Sales Tools](#)

[Find A Rep](#)






DCFT-36-SR7




DCFT-44-SR9




DCFT-54-SR11








DCST-36-SR7



DCST-44-SR9



DCST-54-SR11



MODEL	LENGTH	DEPTH	HEIGHT	STORAGE CAPACITY	COVER STYLE	SYRUP RAIL PUMPS/JARS	HP	VOLT/CYCLE/PHASE	AMPS	NEMA PLUG	SHIP WT.
SLIDE-TOP											
DCST-36-SR7	36	30	36	12 GAL	SLIDE	3P/4J	0.33	115/60/1	3.2	5-15P	385
DCST-44-SR9	44	30	36	18 GAL	SLIDE	4P/5J	0.33	115/60/1	3.2	5-15P	418
DCST-54-SR11	54	30	36	24 GAL	SLIDE	5P/6J	0.33	115/60/1	3.2	5-15P	452
FLIP-TOP											
DCFT-36-SR7	36	30	36	12 GAL	FLIP	3P/4J	0.33	115/60/1	3.2	5-15P	385
DCFT-44-SR9	44	30	36	18 GAL	FLIP	4P/5J	0.33	115/60/1	3.2	5-15P	418
DCFT-54-SR11	54	30	36	24 GAL	FLIP	5P/6J	0.33	115/60/1	3.2	5-15P	452